

FLAMEX® EN 50382-2 FFXS

FLAMEX SI EN 50382-2 Type FFXS 1.8/3 kV 1x150 150°C

Nexans Ref.: 10284128

EAN 13: 3427580835902

Sheathed high temperature flexible shielded Power cables

DESCRIPTION

Application

These cables are designed and dedicated to be used on rolling stock equipment where high temperature is required to save cable weight.

Thanks to its high flexibility, these cables are frequently installed on locomotive equipment with low bending radius.

Construction

- **Conductor**
Extra flexible class 6 copper according to IEC 60228
* tinned copper for 120°C Class
* plain copper for 150°C Class
- **Insulation**
Cross-linked silicone type EI 111 according to EN 50382-1
- **Separator**
Unweaved tape
- **Screen**
Tinned copper wire braid
- **Separator**
Unweaved tape
- **Outer sheath**
Cross-linked silicone type EM 107 according to EN 50382-1
Colour: black outer layer

Marking

FLAMEX SI - EN 50382-2 - Voltage rate (1800V or 3600V) - cross-section mm² - FFXS - temperature class (120°C or 150°C) - NEXANS 279 - week/year

Guide to use

Cabling rules are given according to EN 50343



STANDARDS

International EN 45545-2 (HL3)



Halogen free
EN 50267



Rated Voltage U_o/U
(U_m)
1.8 / 3 kV



Chemical
resistance
Good



Flame retardant
EN 60332-1-2



Fire retardant
EN 50266-2



Smoke density



Gases corrosivity
IEC 60754



Gases toxicity
EN 50305-9.2

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Version 21D Generated 12/2/21 www.nexans.cz Page 1 / 2

FLAMEX® EN 50382-2 FFXS

FLAMEX SI EN 50382-2 Type FFXS 1.8/3 kV 1x150 150°C

- Minimum bending radius (static) : 4 x outer cable diameter
- Minimum bending radius (dynamic) : 6 x outer cable diameter
- Pulling tensible force (dynamic) during installation : 50 N/mm² of copper size
- Mechanical (static) tensible force : 15N/mm² of copper size
- Permissible current carrying capacities : value and calculation method are given in EN 50355

Standards

Construction according to EN 50382-2

CHARACTERISTICS

Construction characteristics

Insulation	High temperature silicone
Halogen free	EN 50267

Dimensional characteristics

Conductor cross-section	150 mm ²
Conductor diameter	15.9 mm
Braid section	11 mm ²
Nominal outer diameter	24.8 mm
Minimum outer diameter	23.6 mm
Maximum outer diameter	26.5 mm
Approximate weight	1657 kg/km

Electrical characteristics

Rated Voltage U _o /U (U _m)	1.8 / 3 kV
---	------------

Usage characteristics

Chemical resistance	Good
Flame retardant	EN 60332-1-2
Fire retardant	EN 50266-2
Smoke density	
Gases corrosivity	IEC 60754
Gases toxicity	EN 50305-9.2
Operating temperature, range	-50 - 120 °C
Max. conductor temperature in service	150 °C



Halogen free
EN 50267



Rated Voltage U_o/U
(U_m)
1.8 / 3 kV



Chemical
resistance
Good



Flame retardant
EN 60332-1-2



Fire retardant
EN 50266-2



Smoke density



Gases corrosivity
IEC 60754



Gases toxicity
EN 50305-9.2

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Version 21D Generated 12/2/21 www.nexans.cz Page 2 / 2